

View Online at <https://aerobasegroup.com/nsn/5340-00-340-4299>

**Mounting Hole Type:**

Threaded

**First Leg Length:**

1.000 inches

**Second Leg Length:**

1.250 inches

**Second Leg Width:**

1.250 inches

**First Leg Hole Diameter:**

0.1380 inches

**Second Leg Hole Diameter:**

0.312 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.430 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.270 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.600 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.230 inches

**First Leg Thickness:**

0.187 inches

**Second Leg Thickness:**

0.187 inches

**First Leg Width:**

0.800 inches

**First Leg Distance Between Hole Centers Along Length:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Second leg one hole is 0.578 in. Dia

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-200/8, t6 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, ty2, cl 2 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-a-8625 spec.