

View Online at <https://aerobasegroup.com/nsn/5340-00-341-0228>

Fabrication Method (non-core):

Stamped

First Leg Length:

0.875 inches

Second Leg Length:

0.875 inches

Second Leg Width:

0.625 inches

First Leg Hole Diameter:

Between 0.098 inches and 0.128 inches

Second Leg Hole Diameter:

Between 0.098 inches and 0.193 inches

Second Leg Distance Between Hole Centers Along Length:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.312 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.312 inches

First Leg Thickness:

0.032 inches

Second Leg Thickness:

0.032 inches

First Leg Width:

0.625 inches

First Leg Distance Between Hole Centers Along Length:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.312 inches

First Leg Distance From Edge To Hole Center Along Length:

0.312 inches

First Leg End Radius:

0.312 inches

Second Leg End Radius:

0.312 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 302

Material Specification:

Mil-s-5059 military specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-s-5059 spec.