NSN 5340-00-341-0228

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-341-0228

Extrinction Method (non-coro):	
Fabrication Method (non-core):	
Stamped	
First Leg Length:	
0.875 inches	
Second Leg Length:	
0.875 inches	
Second Leg Width:	
0.625 inches	
First Leg Hole Diameter:	
Between 0.098 inches and 0.128 inches	
Second Leg Hole Diameter:	
Between 0.098 inches and 0.193 inches	
Second Leg Distance Between Hole Centers Along Length:	
0.500 inches	
Second Leg Distance From Edge To Hole Center Along Width:	
0.312 inches	
Second Leg Distance From Edge To Hole Center Along Length:	
0.312 inches	
First Leg Thickness:	
0.032 inches	
Second Leg Thickness:	
0.032 inches	
First Leg Width:	
0.625 inches	
First Leg Distance Between Hole Centers Along Length:	
0.500 inches	
First Leg Distance From Edge To Hole Center Along Width:	
0.312 inches	
First Leg Distance From Edge To Hole Center Along Length:	
0.312 inches	
First Leg End Radius:	
0.312 inches	
Second Leg End Radius:	
0.312 inches	
First Leg Style:	
End radius	
First Leg Hole Arrangement Style:	
Two holes	
Second Leg Style:	
End radius	
Second Leg Hole Arrangement Style:	
Two holes	

NSN 5340-00-341-0228

Angle Bracket - Page 2 of 2



Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 302

Material Specification:

Mil-s-5059 military specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-5059 spec.