

View Online at <https://aerobasegroup.com/nsn/5340-00-344-2961>

**Fabrication Method (non-core):**

Stamped

**First Leg Length:**

0.980 inches

**Second Leg Length:**

1.179 inches

**Second Leg Width:**

1.702 inches

**Second Leg Corner Radius:**

0.312 inches

**First Leg Hole Diameter:**

Between 0.214 inches and 0.224 inches

**Second Leg Hole Diameter:**

Between 0.339 inches and 0.349 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.078 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.027 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.312 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.240 inches

**First Leg Thickness:**

Between 0.056 inches and 0.068 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.068 inches

**First Leg Width:**

0.560 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.280 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.280 inches

**First Leg End Radius:**

0.500 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 410

**Material Specification:**

Ams 5504 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0