

View Online at <https://aerobasegroup.com/nsn/5340-00-352-0367>

**Fabrication Method (non-core):**

Any acceptable

**Mounting Hole Type:**

Countersunk

**First Leg Length:**

0.625 inches

**Second Leg Length:**

0.688 inches

**Second Leg Width:**

1.000 inches

**Second Leg Corner Radius:**

0.188 inches

**First Leg Hole Diameter:**

Between 0.097 inches and 0.102 inches

**Second Leg Hole Diameter:**

Between 0.146 inches and 0.152 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.625 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.188 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.188 inches

**First Leg Thickness:**

0.040 inches

**Second Leg Thickness:**

0.040 inches

**First Leg Width:**

1.000 inches

**First Leg Corner Radius:**

0.188 inches

**First Leg Distance Between Hole Centers Along Width:**

0.688 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.156 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Nut plate hole in first leg 0.195 in. Nom diameter distance from edge to center along width 0.500 in. Distance from edge to center along length 0.250 in.

**Heat Treatment:**

T-6 solution heat treated

**Material:**

Aluminum alloy 2014

**Material Specification:**

Qq-a-225/4 federal specification single material response

**Surface Treatment:**

Lacquer

**Surface Treatment Specification:**

No. 66 gf14a, fscm 26512 mfr ref single treatment response

**Style Designator:**

Angle

**Specification Data:**

26512-gb11d5-66 manufacturers specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0