

View Online at <https://aerobasegroup.com/nsn/5340-00-352-0367>

Fabrication Method (non-core):

Any acceptable

Mounting Hole Type:

Countersunk

First Leg Length:

0.625 inches

Second Leg Length:

0.688 inches

Second Leg Width:

1.000 inches

Second Leg Corner Radius:

0.188 inches

First Leg Hole Diameter:

Between 0.097 inches and 0.102 inches

Second Leg Hole Diameter:

Between 0.146 inches and 0.152 inches

Second Leg Distance Between Hole Centers Along Width:

0.625 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.188 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.188 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

1.000 inches

First Leg Corner Radius:

0.188 inches

First Leg Distance Between Hole Centers Along Width:

0.688 inches

First Leg Distance From Edge To Hole Center Along Width:

0.156 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Nut plate hole in first leg 0.195 in. Nom diameter distance from edge to center along width 0.500 in. Distance from edge to center along length 0.250 in.

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy 2014

Material Specification:

Qq-a-225/4 federal specification single material response

Surface Treatment:

Lacquer

Surface Treatment Specification:

No. 66 gf14a, fscm 26512 mfr ref single treatment response

Style Designator:

Angle

Specification Data:

26512-gb11d5-66 manufacturers specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0