

View Online at <https://aerobasegroup.com/nsn/5340-00-365-2896>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.977 inches and 1.029 inches

Second Leg Length:

Between 1.610 inches and 1.650 inches

Second Leg Width:

Between 0.380 inches and 0.400 inches

First Leg Hole Diameter:

Between 0.189 inches and 0.204 inches

Second Leg Hole Diameter:

Between 0.189 inches and 0.204 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.190 inches and 0.200 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.180 inches and 0.200 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

Between 0.380 inches and 0.400 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.190 inches and 0.200 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.180 inches and 0.200 inches

First Leg End Radius:

Between 0.380 inches and 0.400 inches

Second Leg End Radius:

Between 0.380 inches and 0.400 inches

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0