# NSN 5340-00-393-1905

Angle Bracket - Page 1 of 2





Mounting Hole Type:
Plain
First Leg Length:
0.406 inches
Second Leg Length:
0.594 inches
Second Leg Width:
1.625 inches
Second Leg Corner Radius:
0.250 inches
First Leg Slot Length:
0.250 inches
First Leg Slot Width:
Between 0.1685 inches and 0.1725 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.250 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.250 inches
Second Leg Slot Length:
0.234 inches
Second Leg Slot Width:
Between 0.170 inches and 0.174 inches
First Leg Thickness:
0.062 inches
Second Leg Thickness:
0.062 inches
First Leg Width:
1.258 inches
First Leg Corner Radius:
0.156 inches
First Leg Distance Between Hole Centers Along Width:
0.500 inches
First Leg Distance From Edge To Hole Center Along Length:
0.156 inches
First Leg Style:
Corner radius
First Leg Hole Arrangement Style:
2 slots
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees

## NSN 5340-00-393-1905

Angle Bracket - Page 2 of 2



### Special Features:

Second leg has one o.126 in. Min, o.127 in. Maximum diameter hole

## Material:

Steel comp 1006 or steel comp 1008 or steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020

#### Material Specification:

Aisi assn standard single material response

### Surface Treatment:

Phosphate

#### Style Designator:

Angle

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A042a0