NSN 5340-00-393-5481

Access Cover - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-00-393-5481

Flat Hole Diameter: Between 0.184 inches and 0.194 inches Width: Between 1.510 inches and 1.530 inches Length: Between 2.410 inches and 2.430 inches Inside Length: Between 1.960 inches and 2.000 inches Corner Radius: Between 0.200 inches and 0.220 inches First Recess Inside Height: Between 0.170 inches and 0.190 inches Inside Corner Radius: Between 0.480 inches and 0.520 inches Body Thickness: 0.050 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-s-5059 spec.	Cross Sectional Shape:
Between 0.184 inches and 0.194 inches Width: Between 1.510 inches and 1.530 inches Length: Between 2.410 inches and 2.430 inches Inside Length: Between 1.960 inches and 2.000 inches Corner Radius: Between 0.200 inches and 0.220 inches First Recess Inside Height: Between 0.170 inches and 0.190 inches Inside Corner Radius: Between 0.480 inches and 0.520 inches Body Thickness: 0.050 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Flat
Width: Between 1.510 inches and 1.530 inches Length: Between 2.410 inches and 2.430 inches Inside Length: Between 1.960 inches and 2.000 inches Corner Radius: Between 0.200 inches and 0.220 inches First Recess Inside Height: Between 0.170 inches and 0.190 inches Inside Corner Radius: Between 0.480 inches and 0.520 inches Body Thickness: 0.050 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Hole Diameter:
Between 1.510 inches and 1.530 inches Length: Between 2.410 inches and 2.430 inches Inside Length: Between 1.960 inches and 2.000 inches Corner Radius: Between 0.200 inches and 0.220 inches First Recess Inside Height: Between 0.170 inches and 0.190 inches Inside Corner Radius: Between 0.480 inches and 0.520 inches Body Thickness: 0.050 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Between 0.184 inches and 0.194 inches
Length: Between 2.410 inches and 2.430 inches Inside Length: Between 1.960 inches and 2.000 inches Corner Radius: Between 0.200 inches and 0.220 inches First Recess Inside Height: Between 0.170 inches and 0.190 inches Inside Corner Radius: Between 0.480 inches and 0.520 inches Body Thickness: 0.050 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Width:
Between 2.410 inches and 2.430 inches Inside Length: Between 1.960 inches and 2.000 inches Corner Radius: Between 0.200 inches and 0.220 inches First Recess Inside Height: Between 0.170 inches and 0.190 inches Inside Corner Radius: Between 0.480 inches and 0.520 inches Body Thickness: 0.050 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Between 1.510 inches and 1.530 inches
Inside Length: Between 1.960 inches and 2.000 inches Corner Radius: Between 0.200 inches and 0.220 inches First Recess Inside Height: Between 0.170 inches and 0.190 inches Inside Corner Radius: Between 0.480 inches and 0.520 inches Body Thickness: 0.050 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Length:
Between 1.960 inches and 2.000 inches Corner Radius: Between 0.200 inches and 0.220 inches First Recess Inside Height: Between 0.170 inches and 0.190 inches Inside Corner Radius: Between 0.480 inches and 0.520 inches Body Thickness: 0.050 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Between 2.410 inches and 2.430 inches
Corner Radius: Between 0.200 inches and 0.220 inches First Recess Inside Height: Between 0.170 inches and 0.190 inches Inside Corner Radius: Between 0.480 inches and 0.520 inches Body Thickness: 0.050 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Inside Length:
Between 0.200 inches and 0.220 inches First Recess Inside Height: Between 0.170 inches and 0.190 inches Inside Corner Radius: Between 0.480 inches and 0.520 inches Body Thickness: 0.050 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Between 1.960 inches and 2.000 inches
First Recess Inside Height: Between 0.170 inches and 0.190 inches Inside Corner Radius: Between 0.480 inches and 0.520 inches Body Thickness: 0.050 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Corner Radius:
Between 0.170 inches and 0.190 inches Inside Corner Radius: Between 0.480 inches and 0.520 inches Body Thickness: 0.050 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Between 0.200 inches and 0.220 inches
Inside Corner Radius: Between 0.480 inches and 0.520 inches Body Thickness: 0.050 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	First Recess Inside Height:
Between 0.480 inches and 0.520 inches Body Thickness: 0.050 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Between 0.170 inches and 0.190 inches
Body Thickness: 0.050 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Inside Corner Radius:
O.050 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Between 0.480 inches and 0.520 inches
Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Body Thickness:
Threaded fastener Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	0.050 inches
Mounting Opening Shape Style: Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Securing Device Type:
Unthreaded hole Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Threaded fastener
Material: Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Mounting Opening Shape Style:
Stainless steel Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Unthreaded hole
Material Specification: Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Material:
Mil-s-5059, type 300 military specification single material response Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Stainless steel
Fsc Application Data: Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Material Specification:
Starter, engine, gas turbine, b52h acft Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Mil-s-5059, type 300 military specification single material response
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Fsc Application Data:
N/a Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Starter, engine, gas turbine, b52h acft
Unit Of Measure: Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	Shelf Life:
Demilitarization: No Fiig: A531c0 Mil-std (military Standard):	N/a
No Fiig: A531c0 Mil-std (military Standard):	Unit Of Measure:
No Fiig: A531c0 Mil-std (military Standard):	
Fiig: A531c0 Mil-std (military Standard):	Demilitarization:
A531c0 Mil-std (military Standard):	No
Mil-std (military Standard):	Fiig:
	A531c0
Mil-s-5059 spec.	Mil-std (military Standard):
•	Mil-s-5059 spec.