

View Online at <https://aerobasegroup.com/nsn/5340-00-395-7398>

Fabrication Method (non-core):

Machined

First Leg Length:

0.840 inches

Second Leg Length:

1.950 inches

First Leg Hole Diameter:

Between 0.216 inches and 0.226 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.312 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 1.030 inches and 1.040 inches

Second Leg Slot Length:

Between 0.800 inches and 0.820 inches

Second Leg Slot Width:

Between 0.216 inches and 0.226 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Distance Between Hole Centers Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

Second Leg End Radius:

0.312 inches

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One slot

First Leg Angle:

84.75 degrees

Material:

Titanium alloy

Material Specification:

Ams 4911 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0