## NSN 5340-00-400-2455

Angle Bracket - Page 1 of 2

First Leg Length:

Second Leg Length:

Second Leg Width:

**Second Leg Hole Diameter:** 

1.875 inches

3.125 inches

4.875 inches

0.344 inches



View Online at https://aerobasegroup.com/nsn/5340-00-400-2455

**Second Leg Distance Between Hole Centers Along Width:** 

| 4.125 inches   |
|--|
| Second Leg Distance Between Hole Centers Along Length:   |
| 1.000 inches   |
| Second Leg Distance From Edge To Hole Center Along Width:  |
| 0.375 inches   |
| Second Leg Distance From Edge To Hole Center Along Length:   |
| 0.375 inches   |
| First Leg Thickness:   |
| 0.250 inches   |
| Second Leg Thickness:  |
| 0.250 inches   |
| First Leg Width:   |
| 4.875 inches   |
| First Leg End Width:   |
| 1.500 inches   |
| First Leg Style:   |
| Square and tapered   |
| First Leg Hole Arrangement Style:  |
| No hole  |
| Second Leg Style:  |
| Square   |
| Second Leg Hole Arrangement Style:   |
| Four holes   |
| Second Leg Relationship To First Leg:  |
| Not identical  |
| First Leg Angle:   |
| 156.0 degrees  |
| Special Features:  |
| 2 additional mtg holes in second leg 0.344 in. Dia, 2.375 in. From end of leg and 0.375 in. From edge                  |
| Material:  |
| Aluminum alloy 6061 or aluminum alloy 5083   |
| Material Specification:  |
| Qq-a-327 federal specification single material response or mil-a-19005 military specification single material response |
|  |
|  |
|  |

## NSN 5340-00-400-2455

Angle Bracket - Page 2 of 2

Mil-a-19005 spec.



| Surface Treatment:                                       |
|--|
| Enamel   |
| Surface Treatment Specification:                         |
| Tt-e-529 federal specification single treatment response |
| Style Designator:  |
| Angle  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A042a0   |
| Mil-std (military Standard):                             |