

View Online at <https://aerobasegroup.com/nsn/5340-00-402-4977>

**First Leg Length:**

Between 1.040 inches and 1.100 inches

**Second Leg Length:**

Between 3.440 inches and 3.500 inches

**Second Leg Width:**

Between 0.590 inches and 0.650 inches

**First Leg Hole Diameter:**

Between 0.550 inches and 0.570 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.300 inches and 0.320 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**Second Leg Slot Length:**

Between 0.600 inches and 0.660 inches

**Second Leg Slot Width:**

Between 0.360 inches and 0.380 inches

**First Leg Thickness:**

0.062 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

Between 0.840 inches and 0.900 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.420 inches and 0.440 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.570 inches and 0.630 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 301

**Material Specification:**

Qq-s-766 temp 1/2 hard federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-std-171 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-std-171 spec.