

View Online at <https://aerobasegroup.com/nsn/5340-00-403-5265>

Fabrication Method (non-core):

Stamped

Mounting Hole Type:

Plain

First Leg Length:

Between 0.508 inches and 0.518 inches

Second Leg Length:

0.770 inches

Second Leg Width:

Between 0.428 inches and 0.448 inches

First Leg Hole Diameter:

Between 0.136 inches and 0.146 inches

First Leg Thickness:

Between 0.071 inches and 0.086 inches

Second Leg Thickness:

Between 0.071 inches and 0.086 inches

Center Section Height:

Between 0.410 inches and 0.430 inches

Center Section Width:

Between 0.428 inches and 0.448 inches

Center Section Thickness:

Between 0.071 inches and 0.086 inches

First Leg Width:

Between 0.428 inches and 0.448 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.209 inches and 0.229 inches

First Leg Distance From Edge To Hole Center Along Length:

0.156 inches

First Leg End Radius:

0.156 inches

First Leg Style:

End radius and tapered

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

No hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

120.0 degrees

Second Leg Angle:

120.0 degrees

Material:

Steel comp 4130

Material Specification:

Fed-std-66 military standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Double angle

Fsc Application Data:

Jet engine, acft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0