

View Online at <https://aerobasegroup.com/nsn/5340-00-409-6805>

**Fabrication Method (non-core):**

Any acceptable

**First Leg Length:**

0.500 inches

**Second Leg Length:**

1.000 inches

**Second Leg Width:**

7.370 inches

**Second Leg Corner Radius:**

0.120 inches

**First Leg Hole Diameter:**

Between 0.242 inches and 0.257 inches

**Second Leg Hole Diameter:**

Between 0.340 inches and 0.349 inches

**Second Leg Distance Between Hole Centers Along Width:**

6.332 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.528 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Thickness:**

0.050 inches

**Second Leg Thickness:**

0.050 inches

**First Leg Width:**

5.000 inches

**First Leg Corner Radius:**

0.120 inches

**First Leg Distance Between First And Second Hole Centers Along Width:**

1.500 inches

**First Leg Distance Between Second And Third Hole Centers Along Width:**

1.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.320 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Three holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 302

**Material Specification:**

Qq-s-766, class 302, cond a federal specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-171 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-s-171 spec.