

View Online at <https://aerobasegroup.com/nsn/5340-00-409-6805>

Fabrication Method (non-core):

Any acceptable

First Leg Length:

0.500 inches

Second Leg Length:

1.000 inches

Second Leg Width:

7.370 inches

Second Leg Corner Radius:

0.120 inches

First Leg Hole Diameter:

Between 0.242 inches and 0.257 inches

Second Leg Hole Diameter:

Between 0.340 inches and 0.349 inches

Second Leg Distance Between Hole Centers Along Width:

6.332 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.528 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.050 inches

Second Leg Thickness:

0.050 inches

First Leg Width:

5.000 inches

First Leg Corner Radius:

0.120 inches

First Leg Distance Between First And Second Hole Centers Along Width:

1.500 inches

First Leg Distance Between Second And Third Hole Centers Along Width:

1.500 inches

First Leg Distance From Edge To Hole Center Along Width:

1.320 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 302

Material Specification:

Qq-s-766, class 302, cond a federal specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-171 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-s-171 spec.