## NSN 5340-00-410-8797

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-410-8797

First Leg Length:

Between 0.440 inches and 0.480 inches

Second Leg Length:

Between 1.330 inches and 1.370 inches

Second Leg Width:

Between 1.493 inches and 1.533 inches

First Leg Hole Diameter:

Between 0.230 inches and 0.250 inches

Second Leg Hole Diameter:

Between 0.210 inches and 0.220 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.210 inches and 0.230 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.210 inches and 0.230 inches

First Leg Thickness:

0.040 inches

**Second Leg Thickness:** 

0.040 inches

First Leg Width:

Between 1.493 inches and 1.533 inches

First Leg Corner Radius:

Between 0.210 inches and 0.230 inches

First Leg Distance Between Hole Centers Along Width:

Between 1.063 inches and 1.073 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.210 inches and 0.230 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.210 inches and 0.230 inches

Second Leg End Radius:

Between 0.210 inches and 0.230 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

**Second Leg Hole Arrangement Style:** 

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

## NSN 5340-00-410-8797

Angle Bracket - Page 2 of 2

Mil-s-5052 spec.



| Material:  |
|--|
| Steel  |
| Material Specification:                                    |
| Mil-s-5052 military specification single material response |
| Style Designator:  |
| Angle  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A042a0   |
| Mil-std (military Standard):                               |