

View Online at <https://aerobasegroup.com/nsn/5340-00-410-8797>

**First Leg Length:**

Between 0.440 inches and 0.480 inches

**Second Leg Length:**

Between 1.330 inches and 1.370 inches

**Second Leg Width:**

Between 1.493 inches and 1.533 inches

**First Leg Hole Diameter:**

Between 0.230 inches and 0.250 inches

**Second Leg Hole Diameter:**

Between 0.210 inches and 0.220 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.210 inches and 0.230 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.210 inches and 0.230 inches

**First Leg Thickness:**

0.040 inches

**Second Leg Thickness:**

0.040 inches

**First Leg Width:**

Between 1.493 inches and 1.533 inches

**First Leg Corner Radius:**

Between 0.210 inches and 0.230 inches

**First Leg Distance Between Hole Centers Along Width:**

Between 1.063 inches and 1.073 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.210 inches and 0.230 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.210 inches and 0.230 inches

**Second Leg End Radius:**

Between 0.210 inches and 0.230 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius and tapered

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel

**Material Specification:**

Mil-s-5052 military specification single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-s-5052 spec.