

View Online at <https://aerobasegroup.com/nsn/5340-00-412-9838>

**First Leg Length:**

0.875 inches

**Second Leg Length:**

1.062 inches

**Reinforcement Method (non-core):**

Rib stiffener both sides

**Second Leg Width:**

0.750 inches

**First Leg Slot Length:**

0.500 inches

**First Leg Slot Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.375 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.438 inches

**Second Leg Slot Length:**

0.500 inches

**Second Leg Slot Width:**

0.250 inches

**First Leg Thickness:**

0.050 inches

**Second Leg Thickness:**

0.050 inches

**First Leg Width:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.375 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.312 inches

**First Leg End Radius:**

0.500 inches

**Second Leg End Radius:**

0.500 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy 2024

**Material Specification:**

Qq-a-250/5, alclad t4 federal specification single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0