

View Online at <https://aerobasegroup.com/nsn/5340-00-412-9839>

First Leg Length:

Between 0.820 inches and 0.830 inches

Second Leg Length:

Between 0.633 inches and 0.643 inches

Second Leg Width:

0.500 inches

First Leg Hole Diameter:

Between 0.200 inches and 0.210 inches

Second Leg Hole Diameter:

Between 0.200 inches and 0.210 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.245 inches and 0.255 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.195 inches and 0.205 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.245 inches and 0.255 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.195 inches and 0.205 inches

First Leg End Radius:

0.500 inches

Second Leg End Radius:

0.500 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0