

View Online at <https://aerobasegroup.com/nsn/5340-00-420-4986>

Fabrication Method (non-core):

Stamped

Mounting Hole Type:

Plain

First Leg Length:

1.128 inches

Second Leg Length:

2.190 inches

Second Leg Width:

3.000 inches

Second Leg Corner Radius:

0.500 inches

First Leg Hole Diameter:

0.406 inches

Second Leg Hole Diameter:

0.406 inches

Second Leg Distance Between Hole Centers Along Width:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Thickness:

0.190 inches

Second Leg Thickness:

0.190 inches

Center Section Height:

1.378 inches

Center Section Width:

3.000 inches

Center Section Thickness:

0.190 inches

First Leg Width:

3.000 inches

First Leg Corner Radius:

0.500 inches

First Leg Distance Between Hole Centers Along Width:

2.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Length:

0.500 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

Second Leg Angle:

30.0 degrees

First Leg Offset Angle:

30.0 degrees

Special Features:

One hole in center of bracket 1.500 in. Dia

Material:

Steel comp 1009 or steel comp 1010 or steel comp 1011 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1023 or steel comp 1025

Surface Treatment:

Enamel

Surface Treatment Specification:

Tt-e-529 federal specification single treatment response

Style Designator:

Offset double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0