

View Online at <https://aerobasegroup.com/nsn/5340-00-425-8664>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.767 inches and 0.799 inches

Second Leg Length:

0.900 inches

Second Leg Width:

Between 0.920 inches and 0.940 inches

Second Leg Corner Radius:

Between 0.109 inches and 0.141 inches

First Leg Hole Diameter:

Between 0.216 inches and 0.220 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.455 inches and 0.475 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.300 inches

Second Leg Slot Length:

Between 0.500 inches and 0.520 inches

Second Leg Slot Width:

Between 0.230 inches and 0.250 inches

First Leg Thickness:

Between 0.071 inches and 0.078 inches

Second Leg Thickness:

Between 0.071 inches and 0.078 inches

First Leg Corner Radius:

Between 0.234 inches and 0.266 inches

First Leg Distance Between Hole Centers Along Width:

0.624 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.234 inches and 0.266 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.234 inches and 0.266 inches

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One slot

First Leg Angle:

95.0 degrees

Material:

Titanium alloy

Material Specification:

Ams 4911 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0