

View Online at <https://aerobasegroup.com/nsn/5340-00-425-8664>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.767 inches and 0.799 inches

**Second Leg Length:**

0.900 inches

**Second Leg Width:**

Between 0.920 inches and 0.940 inches

**Second Leg Corner Radius:**

Between 0.109 inches and 0.141 inches

**First Leg Hole Diameter:**

Between 0.216 inches and 0.220 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.455 inches and 0.475 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.300 inches

**Second Leg Slot Length:**

Between 0.500 inches and 0.520 inches

**Second Leg Slot Width:**

Between 0.230 inches and 0.250 inches

**First Leg Thickness:**

Between 0.071 inches and 0.078 inches

**Second Leg Thickness:**

Between 0.071 inches and 0.078 inches

**First Leg Corner Radius:**

Between 0.234 inches and 0.266 inches

**First Leg Distance Between Hole Centers Along Width:**

0.624 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.234 inches and 0.266 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.234 inches and 0.266 inches

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

One slot

**First Leg Angle:**

95.0 degrees

**Material:**

Titanium alloy

**Material Specification:**

Ams 4911 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0