

View Online at <https://aerobasegroup.com/nsn/5340-00-427-8705>

**Fabrication Method (non-core):**

Machined

**First Leg Length:**

Between 0.900 inches and 0.930 inches

**Second Leg Length:**

Between 0.973 inches and 1.003 inches

**Second Leg Width:**

Between 0.600 inches and 0.640 inches

**First Leg Slot Length:**

Between 0.380 inches and 0.400 inches

**First Leg Slot Width:**

Between 0.208 inches and 0.223 inches

**Second Leg Hole Diameter:**

Between 0.208 inches and 0.223 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.300 inches and 0.320 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.213 inches and 0.223 inches

**First Leg Thickness:**

Between 0.083 inches and 0.097 inches

**Second Leg Thickness:**

Between 0.083 inches and 0.097 inches

**First Leg Width:**

Between 0.600 inches and 0.640 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.295 inches and 0.325 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.200 inches and 0.250 inches

**Second Leg End Radius:**

Between 0.360 inches and 0.390 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel comp 321

**Material Specification:**

Ams 5510 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0