

View Online at <https://aerobasegroup.com/nsn/5340-00-435-5526>

Mounting Hole Type:

Plain

First Leg Length:

0.7400 inches

Second Leg Length:

1.2800 inches

First Leg Hole Diameter:

Between 0.2400 inches and 0.2600 inches

Second Leg Hole Diameter:

Between 0.2130 inches and 0.2240 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.6900 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.4800 inches and 0.5200 inches

First Leg Thickness:

Between 0.0570 inches and 0.0690 inches

Second Leg Thickness:

Between 0.0570 inches and 0.0690 inches

First Leg Width:

1.4200 inches

First Leg Corner Radius:

Between 0.2400 inches and 0.2600 inches

First Leg Distance Between Hole Centers Along Width:

0.9400 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.2400 inches and 0.2600 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.2400 inches and 0.2600 inches

Second Leg End Radius:

Between 0.2200 inches and 0.2600 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

Special Features:

There is two insert with dia. Of 0.4800 in. And hole dia. 0.2800 in. Min. And 0.2870 in. Dia.; thickness min. 0.1800 in. And max. 0.2200 in.; it is made nickel alloy 625 per ams 5666

Material:

Nickel alloy 625

Material Specification:

Ams 5599 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0