

View Online at <https://aerobasegroup.com/nsn/5340-00-435-5526>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.7400 inches

**Second Leg Length:**

1.2800 inches

**First Leg Hole Diameter:**

Between 0.2400 inches and 0.2600 inches

**Second Leg Hole Diameter:**

Between 0.2130 inches and 0.2240 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.6900 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.4800 inches and 0.5200 inches

**First Leg Thickness:**

Between 0.0570 inches and 0.0690 inches

**Second Leg Thickness:**

Between 0.0570 inches and 0.0690 inches

**First Leg Width:**

1.4200 inches

**First Leg Corner Radius:**

Between 0.2400 inches and 0.2600 inches

**First Leg Distance Between Hole Centers Along Width:**

0.9400 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.2400 inches and 0.2600 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.2400 inches and 0.2600 inches

**Second Leg End Radius:**

Between 0.2200 inches and 0.2600 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius and tapered

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**Special Features:**

There is two insert with dia. Of 0.4800 in. And hole dia. 0.2800 in. Min. And 0.2870 in. Dia.; thickness min. 0.1800 in. And max. 0.2200 in.; it is made nickel alloy 625 per ams 5666

**Material:**

Nickel alloy 625

**Material Specification:**

Ams 5599 assn standard single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0