

View Online at <https://aerobasegroup.com/nsn/5340-00-435-5529>

Mounting Hole Type:

Plain

First Leg Length:

0.7400 inches

Second Leg Length:

Between 1.280 inches and 1.320 inches

End Application:

Tf-39 aircraft engine

Second Leg Width:

1.9570 inches

First Leg Hole Diameter:

Between 0.280 inches and 0.287 inches

Second Leg Hole Diameter:

Between 0.213 inches and 0.224 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.4600 inches and 0.4800 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.480 inches and 0.520 inches

First Leg Thickness:

Between 0.057 inches and 0.069 inches

Second Leg Thickness:

Between 0.057 inches and 0.069 inches

First Leg Width:

1.9570 inches

First Leg Corner Radius:

Between 0.240 inches and 0.260 inches

First Leg Distance Between Hole Centers Along Width:

1.717 inches

First Leg Distance From Edge To Hole Center Along Width:

1.0700 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.4800 inches and 0.5200 inches

Second Leg End Radius:

Between 0.240 inches and 0.260 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

1st leg contains 2 spacers made from corrosion resistant steel per ams 5666, 0.460 in. Min to 0.480 in. Maximum diameter, 0.180 in. Min to 0.220 in. Maximum thickness

Material:

Stainless steel

Material Specification:

Ams 5599 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A042a0