NSN 5340-00-436-5016

Helical Compression Spring Seat - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-436-5016

^	^1	ın	to	rh	_	re	D	ia	m	٥ŧ	_	r.
u	οι	JΠ	ιte	110	υ	re	U	ld	ш	eτ	е	Ι.

Between 0.4100 inches and 0.4200 inches

Overall Height:

Between 0.3500 inches and 0.3600 inches

First Step Diameter:

Between 0.4350 inches and 0.4370 inches

First Step Length:

Between 0.0650 inches and 0.0950 inches

Second Step Diameter:

Between 0.5900 inches and 0.6100 inches

Bore Diameter:

Between 0.3120 inches and 0.3140 inches

Material Hardness Rating:

Between 56.0 rockwell c and 60.0 rockwell c

Design Type:

Solid

End Diameter:

Between 0.4000 inches and 0.4200 inches

Distance From End To First Step:

Between 0.0900 inches and 0.1100 inches

Counterbore Length:

Between 0.0850 inches and 0.0950 inches

Special Features:

Not casehardened

Material:

Steel, ams 5643

Material:

Steel comp 630

Material Specification:

Ams 5643 assn standard single material response

Surface Treatment:

Passivate

Style Designator:

Seat

Surface Treatment:

Passivated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5340-00-436-5016

Helical Compression Spring Seat - Page 2 of 2



Fiig:

Т319-е