

View Online at <https://aerobasegroup.com/nsn/5340-00-442-4111>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.625 inches and 0.745 inches

Second Leg Length:

Between 0.750 inches and 0.870 inches

Second Leg Width:

Between 0.720 inches and 0.780 inches

Second Leg Corner Radius:

0.218 inches

First Leg Hole Diameter:

Between 0.218 inches and 0.224 inches

Second Leg Hole Diameter:

Between 0.097 inches and 0.102 inches

Second Leg Distance Between Hole Centers Along Width:

Between 0.365 inches and 0.385 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.280 inches and 0.340 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.150 inches and 0.210 inches

First Leg Thickness:

0.025 inches

Second Leg Thickness:

0.025 inches

First Leg Width:

Between 0.720 inches and 0.780 inches

First Leg Corner Radius:

0.218 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.280 inches and 0.340 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.350 inches and 0.410 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Titanium alloy

Material Specification:

Ams 4911 assn standard single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0