

View Online at <https://aerobasegroup.com/nsn/5340-00-449-1906>

Fabrication Method (non-core):

Stamped

Mounting Hole Type:

Plain

First Leg Length:

Between 0.741 inches and 0.783 inches

Second Leg Length:

Between 0.997 inches and 1.027 inches

First Leg Hole Diameter:

Between 0.200 inches and 0.210 inches

First Leg Thickness:

Between 0.056 inches and 0.058 inches

Second Leg Thickness:

Between 0.056 inches and 0.058 inches

Center Section Height:

Between 0.410 inches and 0.430 inches

Center Section Width:

Between 0.490 inches and 0.510 inches

Center Section Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.195 inches and 0.205 inches

First Leg End Radius:

Between 0.469 inches and 0.531 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Steel comp 321

Material Specification:

Ams 5510 assn standard single material response

Style Designator:

Double angle

Fsc Application Data:

Jet engine, aircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0