

View Online at <https://aerobasegroup.com/nsn/5340-00-449-3403>

Fabrication Method (non-core):

Stamped

Second Leg Length:

Between 0.600 inches and 0.860 inches

Second Leg Width:

0.500 inches

First Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Hole Diameter:

Between 0.276 inches and 0.286 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg Thickness:

Between 0.056 inches and 0.063 inches

Second Leg Thickness:

Between 0.056 inches and 0.063 inches

Center Section Width:

0.500 inches

Center Section Thickness:

Between 0.056 inches and 0.063 inches

First Leg Width:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.240 inches and 0.260 inches

First Leg End Radius:

Between 0.344 inches and 0.406 inches

Second Leg End Radius:

Between 0.344 inches and 0.406 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Material:

Steel comp 410

Material Specification:

Sae51410 federal specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Offset double angle

Fsc Application Data:

Jet engine, acft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0