

View Online at <https://aerobasegroup.com/nsn/5340-00-449-3403>

**Fabrication Method (non-core):**

Stamped

**Second Leg Length:**

Between 0.600 inches and 0.860 inches

**Second Leg Width:**

0.500 inches

**First Leg Hole Diameter:**

Between 0.276 inches and 0.286 inches

**Second Leg Hole Diameter:**

Between 0.276 inches and 0.286 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.240 inches and 0.260 inches

**First Leg Thickness:**

Between 0.056 inches and 0.063 inches

**Second Leg Thickness:**

Between 0.056 inches and 0.063 inches

**Center Section Width:**

0.500 inches

**Center Section Thickness:**

Between 0.056 inches and 0.063 inches

**First Leg Width:**

0.500 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.240 inches and 0.260 inches

**First Leg End Radius:**

Between 0.344 inches and 0.406 inches

**Second Leg End Radius:**

Between 0.344 inches and 0.406 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Material:**

Steel comp 410

**Material Specification:**

Sae51410 federal specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams 2400 assn standard single treatment response

**Style Designator:**

Offset double angle

**Fsc Application Data:**

Jet engine, acft

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0