

View Online at <https://aerobasegroup.com/nsn/5340-00-450-2255>

Center To Center Distance Between Bolt Holes Along Width:

Between 4.865 inches and 4.885 inches

Center To Center Distance Between Bolt Holes Along Length:

Between 6.740 inches and 6.760 inches

Wheel Quantity:

1

Safe Operating Load Rating:

830.0 pounds

Material And Location:

Rubber, hard tread

Surface Treatment And Location:

Any acceptable

Unpackaged Unit Weight:

40.000 pounds

Wheel Type:

Built up

Wheel Diameter:

10.000 inches

Effective Height:

Between 13.000 inches and 13.500 inches

Features Provided:

Axle lubrication fitting and swivel lock and swivel lubrication fitting and brake lock

Plate Style:

Rectangular

Wheel Bearing Type:

Tapered roller

Swivel Bearing Type:

Ball or roller or tapered roller

Swivel Bearing Arrangement:

Two row

Tread Width:

Between 2.938 inches and 3.062 inches

Caster Plate Length:

8.500 inches

Caster Plate Width:

7.000 inches

Caster Plate Mounting Hole Diameter:

Between 0.652 inches and 0.660 inches

Style Designator:

Swivel offset

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A25600