

View Online at <https://aerobasegroup.com/nsn/5340-00-476-6533>

Fabrication Method (non-core):

Cast

First Leg Length:

2.000 inches

Second Leg Length:

2.000 inches

Reinforcement Method (non-core):

Gusset both ends

Second Leg Width:

4.250 inches

First Leg Hole Diameter:

0.391 inches

Second Leg Hole Diameter:

0.328 inches

Second Leg Distance Between Hole Centers Along Width:

2.000 inches

Second Leg Distance From Edge To Hole Center Along Width:

1.125 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.875 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

4.250 inches

First Leg Corner Radius:

0.375 inches

First Leg Distance From Edge To Hole Center Along Width:

2.125 inches

First Leg Distance From Edge To Hole Center Along Length:

1.188 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Nutplate mounted on first leg

Material:

Steel

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl2 federal specification all treatment responses

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0