

View Online at <https://aerobasegroup.com/nsn/5340-00-477-7202>

Center To Center Distance Between Bolt Holes Along Width:

3.375 inches

Center To Center Distance Between Bolt Holes Along Length:

5.250 inches

End Application:

W/s: aircraft, airlifter c-17a; helicopter, carrier based asw, sh-60f; aircraft, starlifter c-141; aircraft, hawkeye e-2c; helicopter, seasprite h-2; aircraft, tomcat f-14; helicopter, search and rescue, hh-60h; helicopter, uscg search and rescue, hh-60j; aircraft, viking s-3b; helicopter, mh-53e; helicopter, advance attack, ah-1w; helicopter, seahawk, h-60

Wheel Quantity:

1

Safe Operating Load Rating:

500.0 pounds

Material And Location:

Rubber tread err-100 err-100

Wheel Diameter:

8.000 inches

Effective Height:

Between 12.994 inches and 13.006 inches

Features Provided:

Shock absorber

Plate Style:

Rectangular

Tread Width:

2.000 inches

Caster Plate Length:

6.750 inches

Caster Plate Width:

5.000 inches

Caster Plate Mounting Hole Diameter:

0.531 inches

Style Designator:

Swivel offset

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A25600