

View Online at <https://aerobasegroup.com/nsn/5340-00-477-7202>

**Center To Center Distance Between Bolt Holes Along Width:**

3.375 inches

**Center To Center Distance Between Bolt Holes Along Length:**

5.250 inches

**End Application:**

W/s: aircraft, airlifter c-17a; helicopter, carrier based asw, sh-60f; aircraft, starlifter c-141; aircraft, hawkeye e-2c; helicopter, seasprite h-2; aircraft, tomcat f-14; helicopter, search and rescue, hh-60h; helicopter, uscg search and rescue, hh-60j; aircraft, viking s-3b; helicopter, mh-53e; helicopter, advance attack, ah-1w; helicopter, seahawk, h-60

**Wheel Quantity:**

1

**Safe Operating Load Rating:**

500.0 pounds

**Material And Location:**

Rubber tread err-100 err-100

**Wheel Diameter:**

8.000 inches

**Effective Height:**

Between 12.994 inches and 13.006 inches

**Features Provided:**

Shock absorber

**Plate Style:**

Rectangular

**Tread Width:**

2.000 inches

**Caster Plate Length:**

6.750 inches

**Caster Plate Width:**

5.000 inches

**Caster Plate Mounting Hole Diameter:**

0.531 inches

**Style Designator:**

Swivel offset

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A25600