

View Online at <https://aerobasegroup.com/nsn/5340-00-480-0281>

Fabrication Method (non-core):

Machined

First Leg Length:

Between 0.697 inches and 0.740 inches

Second Leg Length:

Between 1.353 inches and 1.396 inches

Second Leg Width:

Between 0.609 inches and 0.641 inches

First Leg Hole Diameter:

0.219 inches

Second Leg Hole Diameter:

0.406 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.287 inches and 0.344 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.281 inches and 0.344 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

Between 0.609 inches and 0.641 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.297 inches and 0.328 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.250 inches and 0.313 inches

First Leg End Radius:

Between 0.422 inches and 0.453 inches

Second Leg End Radius:

Between 0.422 inches and 0.453 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0