

View Online at <https://aerobasegroup.com/nsn/5340-00-482-4836>

Fabrication Method (non-core):

Formed

First Leg Length:

1.160 inches

Second Leg Length:

1.340 inches

Second Leg Width:

0.750 inches

First Leg Slot Length:

0.500 inches

First Leg Slot Width:

Between 0.280 inches and 0.310 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.380 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.470 inches

Second Leg Slot Length:

0.620 inches

Second Leg Slot Width:

Between 0.410 inches and 0.440 inches

First Leg Thickness:

0.190 inches

Second Leg Thickness:

0.190 inches

Center Section Height:

2.190 inches

Center Section Width:

0.750 inches

Center Section Thickness:

0.190 inches

First Leg Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.380 inches

First Leg Distance From Edge To Hole Center Along Length:

0.410 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Heat Treatment:

T-6 solution heat treated

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-225/8 federal specification single material response or qq-a-250/11 0 federal specification single material response or qq-a-200/8 0 federal specification single material response

Surface Treatment:

Enamel

Surface Treatment Specification:

Tt-e-489 federal specification single treatment response

Style Designator:

Double angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0