

View Online at <https://aerobasegroup.com/nsn/5340-00-482-4836>

**Fabrication Method (non-core):**

Formed

**First Leg Length:**

1.160 inches

**Second Leg Length:**

1.340 inches

**Second Leg Width:**

0.750 inches

**First Leg Slot Length:**

0.500 inches

**First Leg Slot Width:**

Between 0.280 inches and 0.310 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.380 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.470 inches

**Second Leg Slot Length:**

0.620 inches

**Second Leg Slot Width:**

Between 0.410 inches and 0.440 inches

**First Leg Thickness:**

0.190 inches

**Second Leg Thickness:**

0.190 inches

**Center Section Height:**

2.190 inches

**Center Section Width:**

0.750 inches

**Center Section Thickness:**

0.190 inches

**First Leg Width:**

0.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.380 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.410 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

One slot

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

One slot

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Heat Treatment:**

T-6 solution heat treated

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-225/8 federal specification single material response or qq-a-250/11 0 federal specification single material response or qq-a-200/8 0 federal specification single material response

**Surface Treatment:**

Enamel

**Surface Treatment Specification:**

Tt-e-489 federal specification single treatment response

**Style Designator:**

Double angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0