NSN 5340-00-483-4661

Access Cover - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-483-4661

| Cross Sectional Shape: |
|---|
| Flat |
| Hole Diameter: |
| 0.095 inches |
| Width: |
| 4.097 inches |
| Edge Shape: |
| Rectangle, multi holes |
| Length: |
| 4.995 inches |
| Corner Radius: |
| 0.031 inches |
| Hole Quantity Along Length: |
| 3 |
| Hole Quantity Along Width: |
| 8 |
| Distance Between Holes Along Length: |
| 4.313 inches |
| Distance Between Holes Along Width: |
| 1.550 inches |
| Distance Between Hole Centerline And First Hole Along Length: |
| 0.384 inches |
| Distance Between Hole Centerline And First Hole Along Width: |
| 1.900 inches |
| Distance From First Hole Centerline To End Along Length: |
| 0.096 inches |
| Distance From First Hole Centerline To End Along Width: |
| 0.234 inches |
| Body Thickness: |
| 0.021 inches |
| Securing Device Type: |
| Threaded fastener |
| Mounting Opening Shape Style: |
| Unthreaded hole |
| End Application: |
| Kg-30a, dash10 |
| Material: |
| Steel |
| Surface Treatment: |
| Chromate |
| Onioniale |

Mil-f-14072 military specification single treatment response

Surface Treatment Specification:

NSN 5340-00-483-4661

Access Cover - Page 2 of 2



| • | no | 11 | _ife | • |
|---|----|----|------|---|
| | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A531c0

Mil-std (military Standard):

Mil-f-14072 spec.