

View Online at <https://aerobasegroup.com/nsn/5340-00-485-2119>

**First Leg Length:**

Between 0.625 inches and 0.745 inches

**Second Leg Length:**

Between 0.687 inches and 0.807 inches

**Second Leg Width:**

Between 0.720 inches and 0.780 inches

**Second Leg End Width:**

Between 0.365 inches and 0.385 inches

**First Leg Hole Diameter:**

Between 0.218 inches and 0.224 inches

**Second Leg Hole Diameter:**

Between 0.135 inches and 0.141 inches

**Second Leg Distance Between Hole Centers Along Width:**

Between 0.365 inches and 0.385 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.150 inches and 0.210 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.280 inches and 0.340 inches

**First Leg Thickness:**

0.040 inches

**Second Leg Thickness:**

0.040 inches

**First Leg Width:**

Between 0.720 inches and 0.780 inches

**First Leg End Width:**

Between 0.365 inches and 0.385 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.350 inches and 0.410 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.280 inches and 0.340 inches

**First Leg Style:**

Square and tapered

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square and tapered

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Heat Treatment:**

Full hard

**Material:**

Steel

**Material Specification:**

Mil-s-5059, com+316, 1/4 hard military specification single material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-s-5059 spec.