

View Online at <https://aerobasegroup.com/nsn/5340-00-485-9616>

Fabrication Method (non-core):

Cast

First Leg Length:

Between 0.970 inches and 1.030 inches

Second Leg Length:

Between 0.720 inches and 0.780 inches

Second Leg Width:

Between 1.970 inches and 2.030 inches

Second Leg End Width:

Between 1.470 inches and 1.530 inches

First Leg Hole Diameter:

Between 0.280 inches and 0.287 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.970 inches and 1.030 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.290 inches and 0.350 inches

Second Leg Slot Length:

Between 1.370 inches and 1.430 inches

Second Leg Slot Width:

Between 0.350 inches and 0.410 inches

First Leg Thickness:

Between 0.010 inches and 0.160 inches

Second Leg Thickness:

Between 0.100 inches and 0.160 inches

First Leg Width:

Between 1.970 inches and 2.030 inches

First Leg End Width:

Between 1.530 inches and 1.539 inches

First Leg Distance Between Hole Centers Along Width:

Between 1.240 inches and 1.260 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.345 inches and 0.405 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.305 inches and 0.410 inches

First Leg Style:

Square and tapered

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-200/3 federal specification single material response

Surface Treatment:

Paint

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0