

View Online at <https://aerobasegroup.com/nsn/5340-00-486-7981>

First Leg Length:

Between 0.865 inches and 0.885 inches

Second Leg Length:

Between 1.240 inches and 1.260 inches

Second Leg Width:

0.625 inches

Second Leg Corner Radius:

0.500 inches

First Leg Slot Length:

Between 0.403 inches and 0.413 inches

First Leg Slot Width:

Between 0.322 inches and 0.332 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.312 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.281 inches

Second Leg Slot Length:

Between 0.278 inches and 0.288 inches

Second Leg Slot Width:

Between 0.200 inches and 0.210 inches

First Leg Thickness:

Between 0.056 inches and 0.068 inches

Second Leg Thickness:

Between 0.056 inches and 0.068 inches

First Leg Width:

0.625 inches

First Leg Corner Radius:

0.500 inches

First Leg Distance From Edge To Hole Center Along Width:

0.312 inches

First Leg Distance From Edge To Hole Center Along Length:

0.281 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One slot

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

One slot

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

92.0 degrees

Material:

Steel comp 410

Material Specification:

Ams 5504 assn standard single material response

Surface Treatment:

Passivate

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0