## NSN 5340-00-494-2503

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-494-2503

**Fabrication Method (non-core):** 

Machined

**Mounting Hole Type:** 

Plain

First Leg Length:

Between 0.810 inches and 0.830 inches

Second Leg Length:

Between 1.858 inches and 1.898 inches

Reinforcement Method (non-core):

Gusset both sides

First Leg Hole Diameter:

Between 0.159 inches and 0.164 inches

Second Leg Hole Diameter:

Between 0.204 inches and 0.210 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.320 inches and 0.340 inches

First Leg Thickness:

Between 0.073 inches and 0.087 inches

Second Leg Thickness:

Between 0.073 inches and 0.087 inches

First Leg Distance Between Hole Centers Along Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.820 inches and 0.840 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.320 inches and 0.340 inches

Second Leg End Radius:

Between 0.320 inches and 0.340 inches

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

One hole

First Leg Angle:

90.0 degrees

**Special Features:** 

Color green federal standard 595 no. 34151 outside first leg only

Material:

Steel

**Material Specification:** 

Ams5512 assn standard single material response

## NSN 5340-00-494-2503

Angle Bracket - Page 2 of 2



Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

Fiig:

A042a0