

View Online at <https://aerobasegroup.com/nsn/5340-00-494-7595>

First Leg Length:

Between 0.870 inches and 0.930 inches

Second Leg Length:

Between 1.090 inches and 1.150 inches

Second Leg Width:

Between 1.930 inches and 2.110 inches

Second Leg Corner Radius:

Between 0.280 inches and 0.340 inches

First Leg Hole Diameter:

Between 0.227 inches and 0.233 inches

Second Leg Hole Diameter:

Between 0.128 inches and 0.134 inches

Second Leg Distance Between Lower Hole Centers Along Width:

Between 1.370 inches and 1.430 inches

Second Leg Distance Between Hole Centers Along Length:

0.230 mils and 0.290 centimeters

Second Leg Distance Between First And Second Hole Centers Along Width:

Between 0.670 inches and 0.730 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.280 inches and 0.340 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.280 inches and 0.340 inches

First Leg Thickness:

0.016 inches

Second Leg Thickness:

0.016 inches

First Leg Width:

Between 0.970 inches and 1.030 inches

First Leg Corner Radius:

Between 0.280 inches and 0.340 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.470 inches and 0.530 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.380 inches and 0.440 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Titanium alloy

Material Specification:

Ams 4911 assn standard single material response

Surface Treatment:

Chromate zinc

Surface Treatment Specification:

Tt-p-1757 federal specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0