NSN 5340-00-498-4012

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-00-498-4012

First Leg Length:

Between 0.570 inches and 0.630 inches

Second Leg Length:

Between 0.770 inches and 0.830 inches

Second Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Hole Diameter:

Between 0.176 inches and 0.182 inches

Second Leg Hole Diameter:

Between 0.176 inches and 0.182 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

Between 0.040 inches and 0.060 inches

Second Leg Thickness:

Between 0.040 inches and 0.060 inches

First Leg Width:

Between 0.490 inches and 0.510 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg End Radius:

0.250 inches

Second Leg End Radius:

0.250 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Heat Treatment:

T-3 solution heat treated

NSN 5340-00-498-4012

Angle Bracket - Page 2 of 2

Fiig: A042a0



| Material: |
|--|
| Aluminum alloy 2024 |
| Material Specification: |
| Qq-a-250/5, alclad t3 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Style Designator: |
| Angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |