

View Online at <https://aerobasegroup.com/nsn/5340-00-514-1340>

Mounting Hole Type:

Plain

First Leg Length:

0.685 inches

Second Leg Length:

0.685 inches

Reinforcement Method (non-core):

Rib stiffener center section

Second Leg Width:

0.750 inches

First Leg Hole Diameter:

0.204 inches

Second Leg Hole Diameter:

Between 0.130 inches and 0.135 inches

Second Leg Distance Between Hole Centers Along Width:

0.374 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.188 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.312 inches

First Leg Thickness:

0.064 inches

Second Leg Thickness:

0.064 inches

First Leg Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Width:

0.375 inches

First Leg Distance From Edge To Hole Center Along Length:

0.312 inches

First Leg End Radius:

0.440 inches

Second Leg End Radius:

0.440 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5 federal specification single material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0