

View Online at <https://aerobasegroup.com/nsn/5340-00-515-0569>

Fabrication Method (non-core):

Stamped

First Leg Length:

0.750 inches

Second Leg Length:

1.125 inches

Second Leg Width:

1.125 inches

First Leg Hole Diameter:

Between 0.097 inches and 0.100 inches

Second Leg Hole Diameter:

Between 0.097 inches and 0.100 inches

Second Leg Distance Between Hole Centers Along Length:

0.500 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.040 inches

Second Leg Thickness:

0.040 inches

First Leg Width:

1.125 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

0.562 inches

First Leg Distance From Edge To Hole Center Along Width:

0.250 inches

First Leg Distance From Edge To Hole Center Along Length:

0.250 inches

Second Leg End Radius:

0.250 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

End radius and tapered

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/5 federal specification single material response

Surface Treatment:

Chromate

Style Designator:

Angle

Fsc Application Data:

Spar assembly, center section front, aircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0