

View Online at <https://aerobasegroup.com/nsn/5340-00-515-0754>

**First Leg Length:**

Between 0.585 inches and 0.665 inches

**Second Leg Length:**

Between 0.940 inches and 1.000 inches

**Second Leg Width:**

Between 0.460 inches and 0.540 inches

**First Leg Hole Diameter:**

Between 0.164 inches and 0.244 inches

**Second Leg Hole Diameter:**

Between 0.237 inches and 0.297 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

Between 0.210 inches and 0.290 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

Between 0.710 inches and 0.790 inches

**First Leg Thickness:**

0.051 inches

**Second Leg Thickness:**

0.051 inches

**First Leg Width:**

Between 0.460 inches and 0.540 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.210 inches and 0.290 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.335 inches and 0.415 inches

**First Leg End Radius:**

Between 0.275 inches and 0.355 inches

**Second Leg End Radius:**

Between 0.275 inches and 0.355 inches

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Heat Treatment:**

T-3 solution heat treated

**Material:**

Aluminum alloy 2024 or aluminum alloy 5052

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.