

View Online at <https://aerobasegroup.com/nsn/5340-00-515-0754>

First Leg Length:

Between 0.585 inches and 0.665 inches

Second Leg Length:

Between 0.940 inches and 1.000 inches

Second Leg Width:

Between 0.460 inches and 0.540 inches

First Leg Hole Diameter:

Between 0.164 inches and 0.244 inches

Second Leg Hole Diameter:

Between 0.237 inches and 0.297 inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 0.210 inches and 0.290 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.710 inches and 0.790 inches

First Leg Thickness:

0.051 inches

Second Leg Thickness:

0.051 inches

First Leg Width:

Between 0.460 inches and 0.540 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.210 inches and 0.290 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.335 inches and 0.415 inches

First Leg End Radius:

Between 0.275 inches and 0.355 inches

Second Leg End Radius:

Between 0.275 inches and 0.355 inches

First Leg Style:

End radius

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

End radius

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Heat Treatment:

T-3 solution heat treated

Material:

Aluminum alloy 2024 or aluminum alloy 5052

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.