

View Online at <https://aerobasegroup.com/nsn/5340-00-517-3424>

**Fabrication Method (non-core):**

Stamped

**First Leg Length:**

0.750 inches

**Second Leg Length:**

0.880 inches

**Second Leg Width:**

2.000 inches

**Second Leg Corner Radius:**

0.120 inches

**First Leg Hole Diameter:**

0.250 inches

**Second Leg Hole Diameter:**

Between 0.390 inches and 0.410 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.125 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.440 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.500 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.120 inches

**First Leg Width:**

2.000 inches

**First Leg Corner Radius:**

0.380 inches

**First Leg Distance Between Hole Centers Along Width:**

1.250 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.380 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.380 inches and 0.400 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

150.0 degrees

**Special Features:**

First leg holes threaded 1/4-20 unc-2b

**Material:**

Copper alloy or steel

**Surface Treatment:**

Enamel

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0